

Technical Specifications

Model a508d	DY066A
Processor & Speed	AMD Athlon(B) XP2500+ 1.83GHz/333
Chipset	VIA KM400A
Motherboard	Kelut-GL6E (A7V8X-LA)
RAM	256/2700 MB 333DDR SDRAM
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 512 KB L2 Integrated on Processor module
Hard Drive	40 GB (5400 RPM)
Optical Drive	DVD-ROM Drive: DVD (16x max.) / CD-ROM (48x max.)
Access Speed	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	None
9 in 1 Card Reader	Compact Flash I/II, Memory Stick/PRO, MMC/SD, Smart Media, xD, Microdrive
Video Graphics	AGP 8X, Integrated
Controller	Integrated w/Via KM400 Chipset
Video Memory	64MB UMA
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC658
Chassis	Panther-Lite, 250HV PSU
USB Interface Specification	USB 2.0
External I/O Rear Connectors	4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
External I/O Front Connectors	2=USB, 1= 1394, Line In; Microphone, Headphone, 9 in 1 Card Reader w/USB
Expansion Slots (Total)	3= PCI, 1=AGP
Expansion Slots (FREE)	3= PCI, 1=AGP
Drive Bays (Total)	Two 5.25" external, One 3.5" external, One 3.5" internal
Drive Bays (FREE)	One 5.25" external
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2004
This information is subject to change without notice and
is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct,
indirect, special, incidental or consequential damages
in connection with the use of this material.